



DTS PERFORMANCE DATA


DTS Model	No Load Speed	Operational Speed Range	Continuous Torque	Peak Torque	Continuous Power	Maximum Power	Approximate Size (L x W x H)
DTS 1300	20,000 RPM	1,000 RPM to 15,000 RPM	60 in-oz .42 N-m	310 in-oz 2.2 N-m	.30 HP .22 kW	.74 HP .55 kW	5.8" x 2.6" x 2.3"
DTS 1350	12,000 RPM	1,000 RPM to 12,000 RPM	100 in-oz .65 N-m	360 in-oz 2.5 N-m	.68 HP .50 kW	1.2 HP .9 kW	5.8" x 2.75" x 2.75"
DTS 1500							
DTS 3300	12,000 RPM	1,000 RPM to 12,000 RPM	270 in-oz 1.9 N-m	700 in-oz 5.0 N-m	1.6 HP 1.2 kW	2.03 HP 1.52 kW	8.3" x 3.9" x 3.6"
DTS 3402							10.0" x 3.9" x 3.4"
DTS 3404							12.0" x 3.9" x 3.4"
DTS 4402	8,500 RPM	1,000 RPM to 7,000 RPM	665 in-oz 3.9 N-m	2,100 in-oz 15.00 N-m	3.9 HP 2.9 kW	6.25 HP 4.66 kW	10.0" 5.0" x 4.8"
DTS 4300							8.3" x 5.0" x 5.0"
DTS 4404							12.0" x 5.0" x 4.8"



DTS 1300




DTS 1350




DTS 1500

CANTILEVER MOUNT SPINDLE MODELS




DTS 3300




DTS 4300


OUTBOARD SUPPORT SPINDLE MODELS




DTS 3402



DTS 3404



DTS 4402



DTS 4404



G II Solutions, Inc.
201 Bank Street
P.O. Box 428
Central, SC 29630

Phone: 864.639.6605
Fax: 864.639.4056
E-mail: info@giisolutions.com
Web Site: www.giisolutions.com